

SPILKA TANGO HARDWARE – REPAIRS AND MAINTENANCE

These are guidelines for the repair and maintenance of Spilka Tango patio door hardware. Instructions are provided for the replacement or repair of damaged items or those needing replacement through wear and tear.

QUALITY ASSURANCE AND GUARANTEES

Spilka hardware is produced under a quality control system in accordance with requirements for the NDVK (Norwegian Door- and window control) and AS Spilka Industri has a license from their control body. Below are details of relevant requirements and qualities.

MATERIALS AND ENVIRONMENT

Hardware is used in window construction and thereby as a part of a building's facade. It is important that all items receive relevant initial treatment and that correct maintenance is carried out to ensure continuing operation.

Maintenance requirements may vary dependent on local conditions and should be increased as appropriate.

MAINTENANCE

Hardware is used in window construction and thereby as a part of a building's facade. It is important that all items receive relevant initial treatment and that correct maintenance is carried out to ensure continuing operation. Maintenance requirements may vary dependent on local conditions and should be increased as appropriate.

Lubrication of the espagnolette system

Open the sliding door so you have full access to the espagnolette system.

A few drops of light oil should be applied behind each catch and in the holes by the lockbox. Move the handle to the door repeatedly in open and locked position to cause movement in the catches to ensure the oil spreads. This will prolong the lifespan of the product as well as minimize friction whilst using the door.

